



Shown with optional backlight - loop powered

The BA524E loop powered 4/20mA indicator is a fourth generation field mounting instrument that is electrically and mechanically compatible with the earlier BA524D. It has a much larger full 5 digit display and guaranteed performance between -40 and $+70^{\circ}\text{C}$. Like its predecessor, the BA524E is housed in a robust IP66 enclosure with a separate terminal compartment.

Main application of the BA524E is to display a measured variable in meaningful engineering units within a process area. The zero and span of the display are independently adjustable allowing the indicator to be calibrated to display any linear variable represented by the 4/20mA signal. A root extractor and an adjustable sixteen segment lineariser enable the indicator to display flow and variables such as tank level in linear engineering units. For weighing applications a tare function is included.

The bold 29mm high 5 digit display and 31 segment bargraph provide maximum contrast and have a very wide viewing angle, allowing the BA524E indicator to be easily read in most lighting conditions over a wide temperature range. An optional factory fitted backlight is available for installations in poorly illuminated areas. The five digits, with four decimal points and a negative sign, may be configured to display any variable between -99999 and 99999 .

The robust GRP enclosure has stainless steel fittings, silicone gaskets and an armoured glass window providing IP66 protection between -40 and $+70^{\circ}\text{C}$. Ingress and impact protection have been independently assessed by Intertek. A separate terminal compartment allows the instrument to be installed and terminated without exposing the display electronics.

To further simplify field wiring and subsequent inspection, the terminal cable entries and clamping screws are forward facing. Additional terminals are provided which may be used for linking the return 4/20mA conductor and the cable screens.

A backlight which may be loop or separately powered is available as a factory fitted option. It provides green background illumination allowing the display to be read at night or in poorly illuminated areas. When powered from the 4/20mA loop no additional field wiring is required. Powering from a separate supply produces a brighter backlight but requires additional field wiring.

Optional dual alarm outputs which can switch low power loads, such as sounders, beacons and solenoid valves, are available as a factory fitted option. The two galvanically isolated solid state outputs may be independently conditioned as high or low alarms with normally open or closed outputs. Annunciators on the display show the status of both alarm outputs.

Reliability is ensured by component conformal coating, protection from incorrect connection and radio frequency interference. The indicator has been subjected to extensive vibration testing and is supported by a three year guarantee.

Other field mounting models in this range include the BA504E which has a similar specification and an even larger four digit 34mm high display.

If flammable atmospheres are present either the BA324E or BA324NE should be used. Both have the same features as the BA524E but have been certified for use in hazardous area.

BA524E

2-wire 4/20mA

5 digit indicator

General purpose

- ◆ Loop powered only
1.2V drop
- ◆ 5 digit 29mm high display & 31 segment bargraph
- ◆ IP66 GRP enclosure with separate terminal compartment
- ◆ Root extractor and 16 segment lineariser
- ◆ Optional backlight, alarms & external keypad
- ◆ 3 year guarantee

BEKA

associates


BEKA associates Ltd. Old Charlton Rd.
Hitchin, Hertfordshire, SG5 2DA, U.K.
Tel. (01462) 438301 Fax (01462) 453971
e-mail sales@beka.co.uk www.beka.co.uk

SPECIFICATION


Input	
Current	4 to 20mA
Voltage	Less than 1.2V at 20°C Less than 1.3V at -40°C Less than 5V with optional loop powered backlight.
Overrange	±200mA or ±30V will not damage the indicator.
Display	
Type	Liquid crystal, non-multiplexed 5 digits 29mm high & 31 segment bargraph.
Span	Adjustable between 0 & ±99999 for a 4/20mA input.
Zero	Adjustable between 0 & ±99999 with 4mA input.
Decimal point	1 of 4 positions or absent
Polarity	Automatic minus sign
Zero blanking	Blanked apart from 0 in front of decimal point.
Direction	Display may increase or decrease with increasing 4/20mA input.
Reading rate	2 per second
Bargraph	31 segment 80mm long
Overrange	99999 or -99999 with all decimal points flashing.
Push buttons	
▼	(Function in display mode) Shows display with 4mA input
▲	Shows display with 20mA input
'P'	Displays input in mA or a % of span, has a modified function when alarms are fitted.
'E'	Used for tare function
Accuracy at 20°C	
Linear	±0.02% of span ±1 digit
Root extracting	±16µA at input ±1 digit.
Temperature effect on:	
Zero	Less than 25ppm of span/°C
Span	Less than 50ppm of span/°C
Series mode rejection.	Less than 0.05% of span error for 1mA pk to pk 50 or 60Hz interference.
Environmental	
Operating temp	-40 to +70°C
Storage temp	-40 to +85°C
Humidity	to 95% at 40°C noncondensing
Vibration	Report available
Enclosure	IP66
EMC	Complies with EMC Directive 2004/108/EC.
Mechanical	
Terminals	Screw clamp for 0.5 to 1.5mm ² cable
Weight	1.7kg
Accessories	
Backlight	Green, may be loop or separately powered.
Loop powered	Indicator input voltage 5V
Separately powered	
V supply	11V to 30V dc
I in	35mA
Alarms	Two alarm outputs each of which may be independently configured as a high or low alarm contact with a NO or NC output.
Output	Isolated solid state switch
Vmax	40V dc
Imax	200mA
Ron	5Ω + 0.7V max
Roff	1MΩ min
External keypad	Membrane keypad enables indicator to be controlled without removing cover.
Scale legend	Units of measurement marked onto display escutcheon. #
Tag legend	Tag number or application marked onto display escutcheon. #
Stainless steel legend plate.	Stainless steel plate etched with tag number or application attached to front of the instrument. #
Pipe mounting kit	BA392D or BA393 #

See accessory datasheet for details

DIMENSIONS (mm)



TERMINAL CONNECTIONS



HOW TO ORDER

Model number

Display mode

Display at:

4.000mA

20.000mA

Please specify

BA524E

Linear, root or lineariser*

XXXX } Include position of decimal point,*
XXXX } sign if negative & intermediate
points if lineariser is required.

Accessories

External keypad

Display backlight

Dual alarms

Escutcheon marking

Scale

Tag

Stainless legend plate

Pipe mounting kit

Please specify if required

External keypad

Backlight

Alarms

Legend required

Legend required

Legend required

BA393D or BA393

* Will be set to display 0.0 at 4mA and 1000.0 at 20mA with a linear display if calibration information is not supplied. Can easily be recalibrated on-site.